

# JET®



**Poly-V belt drive system**



**Independent leaf safety guard**



**Moveable power switch with reset and power light**



**5**  
**YEAR** WARRANTY

**Features an XACTA® Fence II System that holds securely to constantly ensure accurate cuts**



## HYBRID STYLE TABLESAW

- **XACTA® Fence II system**  
with T-square design and HDPE sideboards
- **Enclosed cabinet**  
Channels dust to a 4" port for fast, clean dust collection
- **Poly-V belt drive system**  
Reduces vibration and heat build up resulting in better power transfer
- **Left tilting**  
for more controlled beveled cutting
- **Cast iron wings**  
for longer work surface and support area
- **Independent leaf safety guard**  
Protects operator from blade while cutting, even at 45° tilt
- **Moveable power switch with reset and power light**  
lets you customize the position of your on/off switch for convenience, safety
- **Large heavy-duty handwheels**  
Helps you make precise adjustments with less effort

### OPTIONAL ACCESORIES



**Mobile Base**  
708119



**Zero Clearance Insert**  
708791



**Roller Stand**  
709207

Stock Number	708780K
Model Number	JWSS-10CSPF
Table Type	STATIONARY
Right Rip Capacity (in.)	30
Motor (TEFC)	1-3/4HP, 1Ph, 115V
Miter Gauge Type	Standard
Blade Diameter (in.)	10
Arbor Diameter (in.)	5/8
Maximum Depth of Cut (in.)	3-1/3
Maximum Cut Depth at 45° (in.)	2-1/8
Table in Front of Blade at Maximum Cut (in.)	11-1/2
Maximum Cross Cut (in.)	28-1/2
Blade to Front of Table (in.)	11-1/2
Maximum Width of Dado (in.)	13/16
Maximum Dado Diameter (in.) requires zero clearance insert	8
Table Height (in.)	35-1/4
Table Size without Wings (L x W/in.)	21-1/4 x 27
Overall Dimensions (W x D x H/in.)	60 x 40 x 40
Arbor Speed (RPM)	4,000 RPM
Dust Port (in.)	4
Distance Between Sliding Table and Blade (in.)	
Net Weight (lbs.)	409